

Performance Options Delivered

FASSON
Ideas that work for you™

Deliver the Appearance and Performance You Need Fasson® Overlamine Films



Labeling Solutions for Durable Goods

Provide a protective finish, as well as solvent, weathering and abrasion resistance to your printed labels with an overlamine film. Durable labels found in the electronic, automotive, appliance and industrial markets use an overlamine to ensure long-lasting protection. Our comprehensive portfolio includes a variety of high-performance adhesives, with topcoated and print-treated polyesters, and polycarbonate facestocks that are UL and UL-C recognized – plus find some products available Fasson EXACT™.

FASSON OVERLAMINATE FILMS

Topcoated and Print-Treated Films

These products provide a high degree of optic clarity due to their wetout properties. Our topcoated overlaminates provide scratch, abrasion and chemical resistance and are suitable for flexo printing. They also provide excellent thermal transfer printability with resin ribbons. Fasson print-treated products are ideal for use on general purpose press-printed labels requiring scratch, abrasion and chemical resistance and are also thermal transfer imprintable.

Overlamine Decorative Films

Velvet Lexan® films provide chemical and moisture protection as well as scratch and abrasion resistance to finished label constructions. These products feature a matte, non-glare finish in addition to a velvet surface texture making them popular for graphic overlays.

Missing out on polycarbonate nameplate and overlay opportunities? Use our 3 mil or 5 mil products to overlamine a previously printed label construction and achieve the same affect as a subsurface printed label.

FASSON OVERLAMINATE ADHESIVES

Fasson S8020 Global UL Adhesive

Available in U.S., Europe and Asia, this product is manufactured locally and provides excellent yellowing resistance, clarity and UL certification up to 302°F/150°C.

Fasson S730 UL Adhesive

Our industry recognized S730 adhesive is UL recognized up to 302°F/150°C, and is especially suitable when high performance and chemical resistance is required.



Deliver the Appearance and Performance You Need



For a complete listing of our durable components and product constructions, request a copy of our *Durable Product Listing* and our *Durable Product Selector Guide* to assist you through the material selection process.



FASSON FILMS RECOMMENDED FOR OVERLAMINATING APPLICATIONS

	Spec #	Facestock	Adhesive	Liner	Service	MOQ (FT)	Width (IN)	Compliance	Adhesive Feature	
Nameplate/Product ID Protection										
Recommended Print Method	Press Inks	77844	1 Mil Clear Print-Treated PET	S8020	40#BG	Exact	5000/2500	60	UL/C-UL	General Purpose
		77955	1 Mil Clear Print-Treated PET	S8020	1 Mil PET	Exact	2500	60	UL/C-UL	General Purpose/High Clarity
		77856	1 Mil Clear Print-Treated PET	S730	40#BG	Stock	1668	60	UL	High Performance/High Clarity
		77845	2 Mil Clear Print-Treated PET	S8020	40#BG	Custom	4200	60	UL/C-UL	High Performance
	Thermal Transfer	77841	1 Mil Clear PET TC	S8020	40#BG	Exact	2500	60	UL/C-UL	General Purpose
		77842	1 Mil Clear PET TC	S8020	1 Mil PET	Stock	1668	60	UL/C-UL	General Purpose/High Clarity
		77855	1 Mil Clear PET TC	S730	1 Mil PET	Exact	5000	60	UL	High Performance
		77854	2 Mil Clear PET TC	S8020	40#BG	Custom	4200	60	UL/C-UL	General Purpose
Decorative Nameplate Protection										
Non-Printable	77843	1 Mil Matte Pet NTC	S8020	40#BG	Stock	1668	60	UL/C-UL	General Purpose	
	77857	1 Mil Matte Pet NTC	S730	40#BG	Custom	4200	60	UL	High Performance	
	75849	3 Mil Velvet Matte Lexan®	S730	1.5 Mil PET	Exact	1668	54	UL	High Performance/High Clarity	
	75850	5 Mil Velvet Matte Lexan®	S730	1.5 Mil PET	Exact	1668	54	UL	High Performance/High Clarity	

As with any product recommendation, fitness-for-use testing in the actual application is suggested.

FASSON ROLL NORTH AMERICA

8080 Norton Parkway
Mentor, Ohio 44060

800-944-8511
www.fasson.com



© 2008 Avery Dennison Corporation. Fasson® and all other Fasson brands or service programs are trademarks of Avery Dennison Corporation.

1053, 10/08, PDF

WARRANTY

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to the original purchaser to be free from defects in material or workmanship for a period of one year from date of shipment. Purchaser's sole and exclusive remedy for breach of this warranty shall be the replacement of the defective products or, at AVERY DENNISON's option, the issuance of a credit or refund in an amount up to the purchase price of the defective product. In no event shall AVERY DENNISON be responsible for claims beyond the purchase price of the defective product.

THE WARRANTY SPECIFICALLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. IN NO EVENT SHALL AVERY DENNISON BE LIABLE TO PURCHASER OR ANY OTHER PARTY FOR INDIRECT, CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES.

No representative, or agent of AVERY DENNISON is authorized to give any guarantee or warranty or make any representation contrary to the above. No waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and signed by an executive officer of AVERY DENNISON.