

Fasson® NTC LaserCode™ Drum Label/S4600/79#MF

Spec# 78026

Facestock:

Fasson® 4 mil white non-topcoated flexible vinyl. Requires a converter-applied topcoat for ink and toner receptivity.

Basis Weight:	n/a
Caliper:	0.0034 inches ± 10%
Tensile:	MD 3,500 PSI CD 3,000 PSI
Tear:	n/a
Stiffness:	n/a

Adhesive:

Fasson® S4600 is a clear general purpose permanent adhesive featuring good initial tack and ultimate adhesion to a wide variety of substrates.

Type:	Emulsion Acrylic
Minimum Application Temperature:	+10° F
Service Temperature Range:	-40° F to + 300° F subject to facestock limitations

Typical Performance Data: 2 Mil Clear Polyester at room temperature on standard lab panels

Stainless Steel

Loop Tack:	2.77 lbs
Peel Adhesion:	4.1 lbs

Aluminum

Loop Tack:	N/A
Peel Adhesion:	4.4 lbs

Alkyd Enamel Paint

Loop Tack:	N/A
Peel Adhesion:	3.9 lbs

Polypropylene

Loop Tack:	N/A
Peel Adhesion:	4.3 lbs

HDPE

Loop Tack:	N/A
Peel Adhesion:	4.6 lbs

Liner:

79#MF is a machine-finished bleached kraft paper liner. Used primarily for roll-to-sheet applications, including laser. Features good back printability.

Basis Weight:	78# per ream ± 10%
Caliper:	0.0046 inches ± 10%
Tensile:	MD 33# per inch width CD 53# per inch width
Tear:	MD 60 grams CD 75 grams

Total Construction Caliper (approximate): 0.0088 inches ± 10%

Printing and Converting

To maximize on-press efficiencies when converting Fasson® laser film product construction, material should be run with Grain Direction (machine direction) perpendicular to the Feed Direction of laser printing. For a comprehensive list of recommendations for laser products, see "Laser Product Converting Tips" at www.fasson.com. Please read this set of on-line converting tips before purchasing this product: http://na.fasson.com/frna/frnasite.nsf/PG/LNB1C5_NLaser_Guidelines?OpenDocument

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined suitability of such products for its purposes. AVERY DENNISON products are warranted to the original purchaser to be free from defects in material or workmanship for a period of one year from date of shipment. Purchaser's sole and exclusive remedy for breach of this warranty shall be the replacement of the defective products or, at AVERY DENNISON's option, the issuance of a credit or refund in an amount up to the purchase price of the defective product. In no event shall AVERY DENNISON be responsible for claims beyond the purchase price of the defective product.

THE WARRANTY SPECIFICALLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. IN NO EVENT SHALL AVERY DENNISON BE LIABLE TO PURCHASER OR ANY OTHER PARTY FOR INDIRECT, CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES.

No representative or agent of AVERY DENNISON is authorized to give any guarantee or warranty or make any representation contrary to the above. No waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and signed by an executive officer of AVERY DENNISON.

www.na.fasson.com



Avery Dennison
Fasson Roll North America
8080 Norton Parkway
Mentor, OH 44060
800-944-8511 (US & Canada)
52-55-5093-0100 (Mexico)

