

**Data Sheet****FASSON INDIGO PET 50 VOID SILVER MATT / S697 / BG45WH I****Imprint / AMG041****Fasson Specialty****Facestock**

Imprintable matt silver polyester film, with a special absorbent surface coating, "void" printed .

Basis Weight : 71 g/m<sup>2</sup>  
ISO 536  
Caliper : 50 µm  
ISO 534

**Adhesive**

Permanent adhesive / acrylic based.

**Backing**

A supercalendred white glassine paper.

Basis weight : 73 g/m<sup>2</sup> ISO 536  
Caliper : 64 µm ISO 534

**Laminate**

Total caliper : 140µm +/-10%  
Total weight : 171g/m<sup>2</sup> +/- 10%

**Overall Performances**

Tack initial : 560 N/m  
FINAT N°9 (Glass)

Mini Appl. Temp. : +5 °C  
Service Temp. : -40 / +90 °C

N.B. : All data to be considered as typical values.

*Roll Materials Europe*

*July 2007*

*07071311*

**Applications and use**

Adhesive perfectly adapted for uses that need very high label transparence. Very strong final adhesion on a wide range of substrates.

Once applied to the substrate on removal, an irreversible "void" footprint message - will detach itself from the face film. Labels which have been removed cannot be reapplied since repositioning will leave visible proof that tampering has taken place.

Customised footprint messages in the form of text or graphics are available on request.

Preliminary tests have to be done on the substrate in real conditions of use and approved by customers.

NB: it should be noted that the adhesive gramweight is critical to obtain the correct balance of adhesion between substrate and film - especially when labelling varnished carton boards, rough or apolar surfaces.

**Conversion and printing**

The top coated of this face stock allows the printing by HP Indigo presses.

Excellent conversion characteristics on flatbed and rotary presses. The performances of this adhesive with an automatic laying answer to the market needs.

**Shelf life**

2 years at 22 °C and 50 °HR

**Warranty**

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge or AVERY DENNISON may issue credit in such amount as it deems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages. NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.