

Fasson® 1.5 Mil Matte Clear Acetate/S730/50# SCK ABC

Spec# 60091

Facestock:

Fasson® 1.5 Mil Matte Clear Acetate is a cast acetate film with a smooth matte surface. Features a good contact clarity with a low gloss appearance. Recommended for indoor use only.

Basis Weight:	N/A
Caliper:	0.0015 inches ± 10%
Tensile:	MD 8,000 psi CD 9,000 psi
Tear:	N/A
Stiffness:	N/A

Adhesive:

Fasson® S730 adhesive is a clear adhesive featuring good initial tack, high shear, minimal cold flow and ultimate adhesion to a wide variety of substrates.

Type:	Solvent Acrylic
Minimum Application Temperature:	+45° F
Service Temperature Range:	-40° F to +300° F subject to facestock limitations

Typical Performance Data: 2 Mil Clear Polyester at room temperature on standard lab panels

Stainless Steel

Loop Tack:	2.1 lbs
Peel Adhesion:	4.2 lbs

Aluminum

Loop Tack:	N/A
Peel Adhesion:	5.4 lbs

Alkyd Enamel Paint

Loop Tack:	N/A
Peel Adhesion:	3.9 lbs

Polypropylene

Loop Tack:	N/A
Peel Adhesion:	1.7 lbs

HDPE

Loop Tack:	N/A
Peel Adhesion:	0.7 lbs

Liner:

50#SCK is a bleached, super calendered paper stock with very good diecutting and matrix stripping properties. Supplied with an anti-block coating ("ABC") on the backside of the liner. ABC controls adhesive and label transfer to the backside of the liner in finished, wound rolls. This liner should not be used in fanfolded label applications, and is not recommended for back printability.

Basis Weight:	54# per ream ±10% (24 "x 36" 500 sheets)
Caliper:	0.0032 inches ± 10%
Tensile:	MD 48# per inch width CD 26# per inch width
Tear:	MD 50 grams CD 58 grams

Total Construction Caliper (approximate): 0.0056 inches ± 10%

Printing/Converting

This product is printable with most flexographic film inks. This product can be diecut and stripped at high speeds on standard web-fed presses. Sample labels in a variety of shapes have been dispensed and applied successfully with standard labeling systems.

Applications and Uses

This product is suitable for a wide variety of labeling applications including point-of-purchase and tamper evident labeling applications.

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined suitability of such products for its purposes. AVERY DENNISON products are warranted to the original purchaser to be free from defects in material or workmanship for a period of one year from date of shipment. Purchaser's sole and exclusive remedy for breach of this warranty shall be the replacement of the defective products or, at AVERY DENNISON's option, the issuance of a credit or refund in an amount up to the purchase price of the defective product. In no event shall AVERY DENNISON be responsible for claims beyond the purchase price of the defective product.

THE WARRANTY SPECIFICALLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. IN NO EVENT SHALL AVERY DENNISON BE LIABLE TO PURCHASER OR ANY OTHER PARTY FOR INDIRECT, CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES.

No representative or agent of AVERY DENNISON is authorized to give any guarantee or warranty or make any representation contrary to the above. No waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and signed by an executive officer of AVERY DENNISON.

www.na.fasson.com



Avery Dennison
Fasson Roll North America
8080 Norton Parkway
Mentor, OH 44060
800-944-8511 (US & Canada)
52-55-5093-0100 (Mexico)

